

Alargador para pinos DIN 1 e DIN 7978, haste cilíndrica, arraste quadrado, corte à direita, dente helicoidal, hélice à esquerda.

Straight shank taper pin reamer, for taper pins acc. to DIN 1 and DIN 7978, righthand cut, helical flute, helix left.



5502

conicidade 1:50 / taper 1:50 (1°08'45)



Ø nominal d1 mm	Ø menor d3 mm	Ø maior d4 mm	compr. do corte L2 mm	compr. total L1 mm	Ø da haste d2 mm	compr. L3 mm	Z
3	2,9	4,06	58	80	4	5	4
3,5	3,4	4,56	58	80	4		4
4	3,9	5,26	68	93	5		4
5	4,9	6,36	73	100	6,3		4
6	5,9	8	105	135	8		6
7	6,9	9,8	145	180	8		6
8	7,9	10,8	145	180	10	6	
9	8,9	11,8	145	180	10	6	
10	9,9	13,4	175	215	12,5	6	
12	11,8	16	210	255	14	10	6
13	12,8	17	210	255	14		6
14	13,8	18	210	255	14		6
15	14,8	19,4	230	280	18		6
16	15,8	20,4	230	280	18		8
18	17,8	22,8	250	310	20		8
20	19,8	24,8	250	310	22,4	8	
25	24,7	30,7	300	370	28	15	8
30	29,7	36,1	320	400	31,5		8
40	39,7	46,5	340	430	40		10
50	49,7	56,9	360	460	50		10

